

JV200 Series



Eco-solvent entry-level inkjet printer

54"

64"

Wide format outdoor printing at an affordable price

High value in a small footprint, the JV200 provides indoor and outdoor durable printing with a proven 330 printhead, easy-to-use software, and a 3-year peace-of-mind warranty. The perfect entry-level printer.

- Easily produce indoor and outdoor prints on a large selection of media with this outstanding entry-level workhorse.
- Enjoy outstanding quality and productivity, plus the industry's best outdoor durability at an attractive price point.
- The ideal vehicle wrap printer for the money on the market.
- Print a wide range of applications using this complete system that includes software, and a range of ink types, and bulk ink options.
- Easy to use with paired RIP software with complete profiles for all standard media types.
- Outstanding quality and productivity at an attractive price point.
- 3-Year warranty is best in the industry
- Mimaki Core Technologies deliver exceptional results, economically, and with maximum productivity.
- Select from two model widths to suit your production needs.

For best results, always use Mimaki original inks.

Mimaki® JV200 Series

Printhead	On-demand piezo print head (single)	
Print resolution	X: 600, 1200 dpi Y: 600, 900, 1200 dpi	
Print speed (4 color mode)	183 sqft/hr (17 sqm/hr)	
	JV200-130	JV200-160
Maximum print width	53.6 in (1361 mm)	63.4 in (1610 mm)
Maximum media width	53.9 in (1371 mm)	63.8 in (1620 mm)
Weight (uncrated)	284.4 lbs (129 kg)	297.6 lbs (135 kg)
Ink Type/Color	Eco-Solvent inks	
	SS22 (C, M, Y, K, Lc, Lm, Lk, Or)	
Ink Package Size	440ml Cartridges	
	1L Bulk Ink Package (for use with optional Mimaki Bulk Ink System)	
Media Thickness	up to 0.04 in (1 mm) Printing Gap: manual, two settings (1.5, 2.0 mm)	
Media Weight	55 lbs. (25 kg) (with option)	
Certifications	VCCI class A, FCC class A, ETL IEC 62368-1, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH, Energy Star, RCM, EAC, KC, UKCA	
Interface	USB 2.0 Hi-speed Ethernet 1000 BASE-T	
Power Supply	AC (100-120V / 200-240V±10%) × two 50/60Hz±1Hz	
Power Consumption	Max. 1320W x2 Sleep mode: 4.5W	
Operational Environment	Temperature: 68–86 °F (20–30 °C)	
	Humidity: 35–65%	
Dimensions (W x D x H)	JV200-130: 99 in W x 29.5 in D x 54 in H (2520 mm W x 748 mm D x 1370 mm H)	
	JV200-160: 109 in W x 29.5 in D x 54 in H (2770 mm W x 748 mm D x 1370 mm H)	
Options	Mimaki Bulk Ink System, NCU OPT, MBIS BKT OPT	

Eco-solvent entry-level inkjet printer

54"

64"

80 Industrial Drive
Chambersburg, PA 17201
Ph: (855) 927-2465
Visit us at www.apcink.com
MAS-BRO-EQUIP-032



FIND US ON:



Please visit us at: www.mimakiusa.com

Mimaki USA, Inc.
4851 Thurmon Tanner Parkway, Ste. 100 Flowery Branch GA 30542

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications are subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2025, Mimaki USA, Inc.

Rev. 4/11/25