DreamScape® Bling! Specification Sheet v:103025



Heat Aging

Product Name: DreamScape Bling! – 20 oz. (457g/m²) Type II

Description: Commercial grade printable vinyl wallcovering media for modern wide format inkjet printers.

Construction: Embossed vinyl face with laminated fabric backing. Backing is poly-cotton woven

Packaging: 3" core, wound print side out, wrapped in black poly-bag, shipped in heavy-duty cardboard tube

Installation: Standard commercial wallcovering pastes, primers and techniques.

For indoor use in environmentally controlled spaces.

Ink Compatibility: Solvent, eco-solvent, UV curable and HP Latex

Availability:

 Widths:
 54"
 1.37m

 Lengths:
 25yds, 50yds, 100yds
 30m, 50m, 100m

Trial Rolls: 27"x15' .686m x 4.57m

Weight & Thickness:

Product Weight & Thickness: Product Weight: 20oz. per lineal yard (13 oz. per sq yd) 457g/m²

Thickness 0.027in. 0.686mm

Type II Properties: Passes all criterion for WA 101 Type II properties including:

Break Strength Tear Strength Cold Crack

Shrinkage Stain Resistance Coating Adhesion (Bond) Colorfastness Washability Scrubability Blocking Crocking

Specifications: Federal Specification:

CCC-408-D Type II*
WA Specification:

WA-101, NSF/ANSI 342 Sustainability Standard

NFPA Life Safety Code 101*

Fire Test Ratings: ASTM-E84 Tunnel Test Passed Class A

EU Class Flame (EN15102)

BS476 Parts 6&7

CAN/ULC-S102

Passed Class B, s2

Passed all requirements

Passed all requirements

Mold/Mildew: ASTM-G21 Specifications Passed all requirements

Sustainability: NSF-342 - Certified for Silver compliance for all 20 oz wallcovering constructions

HPD – Health Product Declaration available

EPD – Environmental Product Declaration available - UL third party certified for wallcovering industry average

Low VOC – Meets California CDPH Standard for Schools and Offices when tested to CA 01350

Contributes to LEED v4

Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde

Phthalate free formulation Prop 65 compliant

Manufactured without the use of Brominated flame retardants

Warranty: 5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at

http://www.dreamscapewalls.com/

Comments: *Meets or exceeds requirements for flame spread, smoke developed and flashover.