

**7247 Series | Lumina Print Media: Intermediate Calendered, Grey Adhesive**

Lumina 7247 series is an Intermediate grade calendered vinyl film designed for printing general purpose graphics, signage and decals requiring medium-term durability.

**Film Technology** | Calendered (PVC)

**Film Thickness** | 3.4 mil

**Color** | White

**Outdoor Durability** | 3 years

**Finish** | Gloss White (002) Matte White (049)

**Blockout** | Yes

**Adhesive** | Permanent / Gray

**Liner** | 90#

**Conformability** | Flat/Simple Curves

**Shelf Life** | 1 Year

<u><b>CUTTING</b></u>	<u><b>PRINTING</b></u>	<u><b>INSTALLATION</b></u>
<b>Computer Cut</b>   Yes <b>Steel Rule</b>   Yes <b>Thermal Die</b>   Yes <b>Flat Bed</b>   Yes <b>Sheetable</b>   Yes <b>Laminate</b>   Yes / Cold	<b>Thermal Transfer</b>   Yes <b>Solvent</b>   Yes <b>Eco-Solvent</b>   Yes <b>Latex</b>   Yes <b>UV</b>   Yes <b>Screen</b>   Yes	<b>Wet Apply</b>   Yes <b>Min. App. Temp.</b>   40°F <b>Interior / Exterior</b>   Yes

<p><b><u>FILM</u></b></p> <ul style="list-style-type: none"> <li>• <b>Film Thickness</b>__ (mils/μm) 3.4 Mil</li> <li>• <b>Film Weight</b>__ (gsm) 104</li> <li>• <b>Gloss</b>__ 60° Reflection (25 to 40 Gloss Units)</li> <li>• <b>Opacity</b>__ (%) 96</li> <li>• <b>Tensile Strength</b>__ (lbs/in) MD &gt; 3500 / CD &gt; 3500</li> <li>• <b>Elongation</b>__ (%) MD &gt; 200 / CD &gt; 200</li> <li>• <b>Dimensional Stability</b>__ (FTM 14) MD &lt; 2.00 mm / CD &lt; 1.20 mm</li> </ul>	<p><b><u>ADHESIVE</u></b></p> <ul style="list-style-type: none"> <li>• <b>Adhesive Type</b>__ gray pigmented permanent acrylic</li> <li>• <b>Adhesive Thickness</b>__ (mils/μm) N/A</li> <li>• <b>Adhesive Color</b>__ Gray</li> <li>• <b>Peel Strength</b>__ (lbs/in) (N/25mm) 24 hrs. 4.4 lbs./inch</li> </ul>
<p><b><u>LINER</u></b></p> <ul style="list-style-type: none"> <li>• <b>Liner Weight</b>__ (#/gsm) 90</li> <li>• <b>Liner Type</b>__ poly-coated bleached kraft</li> <li>• <b>Liner Thickness</b>__ (mils/μm) N/A</li> <li>• <b>Release Force</b>__ @ 360" / min (g/2") 30-70</li> </ul>	<p><b><u>PERFORMANCE GUIDANCE</u></b></p> <ul style="list-style-type: none"> <li>• <b>Application Temp.</b>__ On clean, dry substrate &gt; +50 °F</li> <li>• <b>Service Temp.</b>__ -40 °F to 180 °F</li> <li>• <b>Shelf Life</b>__ up to 1 year</li> <li>• <b>Storage Temp. / Rel. Humidity</b>__ 70°F (21°C) and 50% relative humidity</li> <li>• <b>Outdoor Durability</b>__ up to 3 years</li> </ul>

NOTE - For further information regarding printing, substrate cleaning, application, maintenance, durability, and removal please review the corresponding instructional bulletin available at [fdcfilms.com](http://fdcfilms.com).

WARRANTY - Data provided by FDC Graphic Films, Inc. is for general information only. This data is not to be used for exacting specification purposes. Always pre-test the product. Suitability for any given application is the responsibility of the user. Since FDC Graphic Films, Inc. cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety, or applicability with respect hereto. FDC Graphic Films, Inc.'s only obligation shall be to replace such a quantity of product proven to be defective. FDC Graphic Films, Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC Graphic Films, Inc., shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, to short or reduced supply of fuel, or other integral components of the product.

<MA>